

facsimile

TRANSMITTAL

Date: June 30, 2003

No. of Pages: 33 (including this cover sheet)

Fax No.: (703) 305-1341

PLEASE DELIVER THE FOLLOWING PAGES IMMEDIATELY TO:

Name: Commissioner of Patents

Art Unit: 2834

Examiner: Burton S. Mullins

Phone: (703) 305-7063

From: Richard J. Ward, Jr.
Reg No. 24,187

Re: Application No. 09/752,975: Filed December 27, 2000
Entitled GRAVITATIONAL WAVE GENERATOR UTILIZING
SUBMICROSCOPIC ENERGIZABLE ELEMENTS

File: 40702/RJW/B596

I HEREBY CERTIFY THAT THIS PAPER IS BEING FACSIMILE TRANSMITTED TO
THE UNITED STATES PATENT AND TRADEMARK OFFICE ON ~~June 30, 2003~~

FAX RECEIVED


Margaret A. Sullivan

JUN 30 2003

TECHNOLOGY CENTER 2800

*Correspondence: Substitute Specification Compare

*Correspondence:

For Office Services Use Only
R turn to Carol Burchfield

Christie, Parker & Hale, LLP
350 West Colorado Boulevard
Post Office Box 7068
Pasadena, CA 91109-7068
626-795-9900
Fax: 626-577-8800

confidential

The information in this transmission is confidential and is intended only for the use of the individual or entity named above. If the reader of this message is not the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is prohibited. If you have received this communication in error, please notify us immediately by telephone collect, and return the original message to us at the above address via U.S. mail. We will reimburse you for postage. Thank you.

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION**GRAVITATIONAL WAVE GENERATOR UTILIZING
SUBMICROSCOPIC ENERGIZABLE ELEMENTS**

5

REFERENCE TO RELATED APPLICATIONS.

This application is a continuation-in-part of Application
Serial No. 09/616,683, filed July 14, 2000, [now U.S. Patent
6,417,597, July 9, 2002,] which is a continuation-in-part of
10 [Serial No. 09/443,257, filed November 19, 1999, now] U.S. Patent
6,160,336, ~~issue date~~ December 12, 2000.

BACKGROUND OF THE INVENTION

This invention relates to the generation, refraction and
15 detection of high-frequency gravitational waves that can be
modulated and utilized for communications, propulsion and for the
purpose of testing new physical [and astronomical] theories,
concepts, and conjectures. More particularly the invention
relates to the generation of gravitational waves (GW) by the
20 interaction of submicroscopic energizing and energizable elements
(molecules, atoms, nuclei, nuclear particles, [electrons,]
photons, antiprotons, etc.). The invention also relates to the
use of forces such as electromagnetic or nuclear to impart a
third-time derivative [or oscillatory] motion to a mass
25 consisting of a collection [of submasses or mass-pairs] of
energizable elements such as target nuclei.

The nuclear forces, which are approximately one-hundred
times stronger than electromagnetic forces, are occasioned by the
interaction of an energizing mechanism such as a submicroscopic
30 particle beam with a ~~mass consisting of a~~ collection of
energizable elements such as target nuclei, which can be aligned
with each other, or with another particle beam whose particles
can also be aligned. Upon interaction with the particle beam or
some other energizing mechanism, some of the nuclei are triggered
35 by the impacting particles to produce a nuclear reaction thereby

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

generating an impulse, that is, undergo a reactive jerk or [a]
harmonic oscillation. The resulting reactive jerk or harmonic
5 oscillation of the ensemble of target nuclei or other energizable
elements acting in concert in turn generates a gravitational wave
(GW).

The general concept of the present invention is to simulate
or emulate GW generated by energizable ~~astrophysical~~ [celestial]
10 systems (rotating binary stars, star explosions, collapse of [to]
black holes, etc) by the use of micro, terrestrial energizable
systems. Such terrestrial systems generate well over 40 orders
of magnitude more force intensity (nuclear or electromagnetic
compared to gravitational) and well over 12 orders of magnitude
15 greater frequency (THz compared to [1 Hz or a small fraction of
1] Hz) than the ~~astrophysical~~ [celestial] systems. Terrestrial
energizable systems produce significant and useful GW according
to the various embodiments of the present invention, even though
they are orders of magnitude smaller than extra-terrestrial,
20 ~~astrophysical~~ [celestial] systems. In the various embodiments
of the present invention the large number of small energizable
elements are energized in a sequence or in concert by energizing
elements emulating the motion of a much larger and extended body
[having a larger radius of gyration] in order to enhance the
25 generation of GW. [The laboratory generation of GW was discussed
by Pinto & Rotoli in *General Relativity and Gravitational
Physics*, 1988, World Scientific, Singapore. They found (page
560) terrestrial laboratory GW generation to be "...at the limit
of the state of the art...", but they did not consider
30 submicroscopic, specifically nuclear particles and associated
forces and did not discuss the jerk mechanism for generating GW
or computer control.]

DESCRIPTION OF PRIOR ART

35

40702/RJW/B596

SUBSTITUTE SPECIFICATION

Robert M. L. Baker, Jr. in Application Serial No. 09/616,683, filed July 14, 2000, entitled Gravitational Wave Generator, [now U.S. Patent 6,417,597,] teaches that a third time derivative or jerk of a mass generates gravitational waves (GW) or produces a quadrupole moment (~~harmonic oscillation~~) and that the GW energy radiates along the axis of the jerk or [if a harmonic] oscillation or[, then radiates] in a plane normal to the axis [of the oscillation]. The force producing such a jerk or oscillation can be gravitational attraction, centrifugal, electromagnetic, nuclear, or, in fact, any force. The magnitude of the jerk or, more specifically, the magnitude of the third time derivative of the moment of inertia of the mass squared, determines the magnitude of the generated GW [determined, for example by a quadrupole approximation]. This latter quantity is approximately equal to the product of a very small coefficient and the square of a kernel or fraction consisting of [twice] the radius of gyration of the mass times the change in force divided by the time interval required to create the force change. The force energizing mechanism can be a particle beam. The particle-beam frequency is that resulting from chopping the particle beam into bunches. The magnitude of the GW power is approximately proportional to the square of the kernel according to the general theory of relativity as discussed in the Baker patent application Serial No. 09/616,683, filed July 14, 2000[, now U.S. Patent 6,417,597]. Transmission of modulated GW and subsequent detection enable use of GW in communications applications.

A preferred embodiment of the invention relies on the use of aligned target nuclei wherein the nuclear reaction attendant upon the collision of the particle-beam particles with the nuclei releases its products in a preferred direction in space so that all target nuclei act in concert to produce a jerk or harmonic oscillation of the target mass and accumulatively generate a GW.

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

Thus related to the GW generation process, but not the process
itself, is the containment system to produce nuclei alignment.
5 That system and process is described in three patents by Henry
William Wallace, 3,626,605, 3,626,606, and 3,823,570 and
incorporated herein by reference. Applicable to the GW
communications applications is the ability to measure small
voltages and currents by a superconducting quantum interference
10 device or SQUID, that is described, for example, by Michael B.
Simmonds in U.S. Patent 4,403,189 and incorporated herein by
reference. Another useful technique, termed quantum
non-demolition, or QND, is also applicable to the GW
communications applications and is described by Harry J. Kimble,
15 et al. in U.S. Patent 4,944,592 and incorporated herein by
reference. QND facilitates the communication application by
avoiding quantum mechanical difficulties.

20

25

30

35

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION**SUMMARY OF THE INVENTION**

The present invention provides the generation of
5 gravitational waves (GW) caused by the interaction of
submicroscopic (molecules, atoms, nuclei, nuclear particles,
[electrons,] photons, etc.) energizing and energizable elements.
This interaction involves electromagnetic forces or nuclear
forces. The important feature of the interaction is that the
10 inertial mass of the energizable elements, taken as a whole, is
caused to jerk or harmonically oscillate and thereby generate GW.
A presently preferred embodiment of the present invention
utilizes strong nuclear forces that are attendant to a nuclear
reaction triggered or energized by the impact of a submicroscopic
15 energizing particle, such as a photon, electron, proton, neutron,
antiproton, alpha particle, etc. from a high-frequency pulsed
particle beam incident on a target mass composed of energizable
elements such as atomic nuclei. In the preferred embodiment, the
nuclei are aligned or constrained as to spin or some other
20 nuclear condition by being placed in an electromagnetic field,
in a superconducting state, spin polarized, etc. This results
in the products of all of the nuclear reactions being emitted in
[approximately] the same preferred direction. Each emission
results in a recoil impulse on the nuclei or a rapid build up of
25 force that jerks the nuclei or causes them to harmonically
oscillate and results in an emission of gravitational waves or
wave/particles also called ~~A force cone or~~
~~Anassons~~ ["gravitational instantons."] The particles in the
beam are chopped into very small bunches, that is, with[, for
30 example,] GHz to THz frequency, so that a very rapid force build
up or jerk is produced in the target mass, that is, in the target
nuclei, resulting in a GW exhibiting the chopping frequency. The
impulse can also be accomplished without nuclei alignment by
other means, such as molecular [or high-energy nuclear] beam
35 particle collision with unaligned target nuclei [or by impressing

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

a high-frequency magnetic field on a high-temperature
superconductor]. Since gravitational waves in, for example, a
5 superconductor move significantly slower than light speed, the
particles of the beam can be accelerated to this GW speed and
move through the ensemble of target nuclei, which compose the
target mass, in step with the forward-moving or radially-moving
gravitational wave. Thus, the forward-moving or radially-moving
10 gravitational wave (GW) builds up amplitude as the particles of
the beam move through the target particles in concert to generate
coherent GW and emulate a much larger target mass. By varying
the number of particles in each bunch of particles in the
particle beam and the chopping frequency, both the beam and the
15 gravitational waves produced by it can be modulated and carry
information. The target mass or collection of target nuclei can
be a solid, a liquid (including a superfluid such as liquid
helium II), a gas (including an electron gas) or other particle
collection.

20

25

30

35

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a diagram of the impact of a particle beam 1 with
5 a target mass 9 resulting in the generation of gravitational
waves having axis 21.

FIG. 1B is a diagram of bunches of particles 12 in a
particle beam interacting with another incoming particle bunch
13 resulting in the generation of gravitational waves having an
10 axis 21.

FIG. 2 is a diagram of GW 21, passing through a medium that
refract GW 34 and causes the GW to bend 35 as it traverses the
surface of the medium 38 and can be focused.

FIG. 3A is a diagram of an energizing particle 41 impacting
15 an energizable particle 40 resulting in the generation of a
cylindrical GW or GW ring 43.

FIG. 3B is a diagram of a subsequent impact with other
particles 44 resulting in GW 45 that reinforces the GW 43.

FIG. 3C is a diagram of another subsequent impact with other
20 particles 46 resulting in GW 47 that reinforces the GW 43 and 45.
[

]FIG. 3D is a diagram of yet another subsequent impact with
other particles 48 resulting in GW 49 that reinforces the GW 43,
45, and 47.

25 FIG. 4 is a diagram of energizable particles 50, 54, 56 and
58 releasing linear [or plane-wave] GW 53, 55, 57, and 59 that
result in a build up or reinforcement of GW 62.

FIG. 5 is a diagram of a particle source 15 that can be
accelerated by an acceleration device 16, focused by a focusing
30 device 17 and separated into bunches by a chopping device 18.
The chopping device is controlled by a computer 19, an
information-processing device 20, and a transmitting device 71.
The particle bunches 1 energize target particles 9 and result in
GW having axis 21 and capable of being received by a receiving
35 device 70.

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

FIG. 6A is a plan view of an array of energizable elements such as 28 whose relative location is denoted by 27.

5 FIG. 6B is a diagram of an array of energizable elements, members of which 26 are energized as the crest or front of a GW 25 passes by resulting in a reinforced GW having a directivity angle of ~~180E~~ [180°].

10 FIG. 6C is a diagram of the array of FIG. 6B with a directivity angle is ~~135E~~ [135°].

FIG. 6D is a diagram of the array of FIG. 6B with a directivity angle is ~~90E~~ [90°].

FIG. 6E is a diagram of the array of FIG. 6B with a directivity angle is ~~45E~~ [45°].

15 FIG. 6F is a diagram of the array of FIG. 6B with a directivity angle is ~~0E~~ [0°].

FIG. 7 is a diagram of various elements 31 that are spread out over a sphere 33 that results in either the generation or detection of GW with directivity.

20 FIG. 8 is a block diagram of a propulsion system utilizing a gravitational wave generator according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

25 In FIG. 1A, in the preferred embodiment, an incoming particle beam 1 impacts a target mass 9 through its containment surface 23 resulting in a nuclear reaction or collision and the generation of GW exhibiting an axis 21, which can propagate radially or in either direction. The reaction or collision also
30 produces back scattered particles 2, nuclear reaction products 3 moving in the preferred direction of target nuclei alignment 22, high-energy photons 4 (for example, x-ray emissions) also moving primarily in the preferred direction 22, sputtered particles 7, and recoil atoms 8. A typical target atom 11 when
35 impacted by the particle beam is jerked by the release of

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

5 nuclear-reaction products or by collision or by other means and
produce GW similar to or in simulation of a sub-microscopic
star explosion or collapse [discussed by Geoff Burdge, Deputy
Director for Technology and Systems of the National Security
Agency, written communication dated January 19, 2000 and
incorporated herein by reference]. This axis is described and
10 illustrated co-pending Patent Application, Serial No. 09/616,683,
filed July 14, 2000[, now U.S. Patent 6,417,597. In the case of
nuclear-reaction-produced jerks, the radius of gyration at the
reactants is significantly smaller than the GW wavelength so that
the quadrupole approximation holds]. The energizing process can
also result in harmonic oscillation or a quadrupole radiator.
15 In this case the GW propagates radially or cylindrically as
discussed by Albert Einstein and Nathan Rosen (1937, Journal of
the Franklin Institute, 223, pp. 43-54). The ~~target-s~~ [target's]
characteristic length, absorption depth, or approximate radius
of gyration of the extensive emulated target mass 10 is utilized
20 in the quadrupole approximation to compute the power of the GW
that is generated.

In FIG. 1B, the particle bunches 12 are shown impacting or
colliding with an incoming particle bunch 13 of another particle
beam at a collision angle 14, which could be any value including
25 zero. In this case, the incoming target bunch is contemplated
to be spin-polarized noble gas, such as helium II or odd-nuclear
isotopes of xenon, etc. in order to exhibit a preferred direction
in space 22.

In FIG. 2 is exhibited a medium in which the GW speed is
30 reduced 34, the new direction of GW 35 caused by the GW passing
through a boundary of a medium 38 at an oblique angle 36 with
respect to a normal to the surface of such a medium 37 produces
GW refraction. The back surface of the medium in which the GW
speed is again changed 39 is shown, but for clarity no refractive

35

1 40702/RJW/BS96

SUBSTITUTE SPECIFICATION

bending of the GW is exhibited. Examples of suitable media are superconducting media.

5 In FIGS. 3A, 3B, 3C, and 3D are exhibited the build up or accumulation of GW along the radially expanding cylindrical GW wave fronts created by and normal to the motion direction 42 of the energizable particle or quadrupole radiator axis. In FIG. 3A a typical central target-mass particle 40 is energized by an
10 incoming particle 41 of the particle-beam bunch. The radially expanding GW wave front 43 moves out at local GW speed.

In FIG. 3B, which is at a time Δt later, where Δt is the time between the arrival of the first and second particle bunch, that is, inversely proportional to the beam-chopping frequency.
15 In this case GW 43 emanating from the first typical target-mass particle 40 is reinforced or constructively interferes with the GW generated by other target-mass particles 44 situated at the distance $V_{GW}\Delta t$ radially out from target-mass particle 40, where V_{GW} is the local GW speed. For clarity only two particles 44 are
20 exhibited out of a ring of such target particles in the target mass in a plane normal to the direction of the energizing motion. Their location will be such as to cause their GW 45 to constructively interfere with and reinforce the originally expanding GW 43.

25 In FIG. 3C, which is at time $2\Delta t$ later, the GW 43 emanating from the first particle 40 and the second particles 44 are reinforced by another set of particles 46 and their attendant GW 47. FIG. 3D is at time $3\Delta t$ and typical target-mass particles 48 add their GW 49 to the accumulating and radially expanding GW.
30 Each arriving beam bunch initiates additional expanding rings of coherent GW until the target-mass particles are exhausted or until their replacements are unavailable. There are large numbers of energizable particle sites that are simultaneously energized so that the GW permeates the target mass as the GW are
35 superimposed. [As noted by Pinto & Rotoli (op cit, p. 567)

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

5 "...the quadrupole formula is only valid provided a suitable surface integral vanish(es), which is the case for an assembly of point sources,...".]

10 In the context of the previous Application, Serial No. 09/616,683, [now U.S. Patent 6,417,597,] the typical target-mass, particles such as 40, 44, 46, and 48 are considered to be energizable elements. Such elements can be permanent magnets, electromagnets, [solenoids (or nanosolenoids)] current-carrying plates, piezoelectric crystals, nanomachines including harmonic oscillators, nanomotors and nanosolenoids or microelectromechanical systems (MEMS) and nanoelectromechanical systems (NEMS) in general, etc. [In the case of solenoids (or nanosolenoids), some nanomachines, nanoelectromechanical systems, 15 current-carrying plates, etc. the energizing and energizable elements can be colocated, for example the energizing coil around the energizable central magnetic core in the case of the nanosolenoids.]

20 The energizing elements in the context of the '683 application would include coils, current pulses moving in conductors, biomolecular motors, etc. that operate under the control of an Individual Independently Programmable Coil System (IIPCS), described in the parent Patent 6,160,336 of which the 25 previous Application[, now U.S. Patent 6,417,597,] is a continuation-in-part, in order to activate or energize the energizable elements in a sequence as the ring of GW, whose propagation plane is normal to the direction of the energizable elements quadrupole radiator axis, moves radially out at local 30 GW speed. In this case directivity can be achieved in both the orientation of the GW ring's plane, the sector of that expanding ring where the GW wave front is reinforced or constructively interfered with by energizing the energizable elements and/or by destructive interference of one GW with another (as in the 35 astrophysical case of a uniformly, isotropically exploding or

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

collapsing star). The collector elements, in the context of the previous application, Serial No. 09/611,683[, now U.S. Patent
5 6,417,597] would be at the same locations as the energizable elements and interrogated in a sequence by the IIPCS to detect or receive specific GW frequencies, that is, tuned to the GW frequency.

In FIG. 4 the constructive interference or reinforcement or
10 amplification of a GW by energizable elements is over a linear pattern 50, 54, 56, and 58 produced by a micro mass explosion or collapse which simulate a macro star explosion or collapse, with GW directed along its axis as predicted by ~~Budge, ibid,~~ [Burdge, op. cit.] 2000 is illustrated [(but directed in both directions
15 along the axis)]. The reinforcement of GW is illustrated schematically by the arrows 53, 55, 57, and 59. The GW builds up to a larger amplitude 62 as the beam bunch and the GW crest or front move with the same speed together through the particles comprising the target mass and generate coherent GW pulses. The
20 target particles or energizable elements 50, 54, 56 and 58 are VGW Δt apart where VGW is the GW speed and Δt is the time between energization. Thus an extensive mass composed of all of the energized target particles is emulated. In the context of th
>683 application['597 patent] the typical target mass particles
25 50, 54, 56 and 58 are considered to be energizable elements. As already discussed, such elements can be magnets, conductors, piezoelectric crystals, harmonic oscillators, nanomachines, etc. The collector elements, in the context of >683['597], would be at the same locations as the energizable elements and
30 interrogated in a sequence by the IIPCS to detect or receive GW having a particular frequency and phase.

In FIG. 5, of the preferred embodiment a particle source 15, which could be a laser or a nuclear reaction, produces particles that can be accelerated by an acceleration device 16 (unless the
35 particles are photons), focused by a focusing device 17 such as

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

a superconducting fluid [medium or electromagnetic field] and separated into bunches by a beam chopper 18. The target mass can be a solid, a liquid (including a superfluid such as liquid helium II), a gas (including electron gas), or another particle beam. Alternately, the beam can be separated into bunches and modulated as to frequency and number of particles in each bunch at the particle source 15. The particle source [15 or beam chopper 18] is controlled by computer 19, an information-processing device 20 and transmitter 71. The particle beam bunches 1 impact the target particles 9 and produce a nuclear reaction, generating GW 21, which can be received at receiving device 70. The information processing device 20 can be, for example, a Kalman filter and/or a table look up for identifying the element to be energized.

In FIG. 6A, are illustrated a plan view of a typical stack of elements or array of element sets or subsets, which could be GW collectors or could be energizable elements such as target atoms or nuclei. The indices, which describe the location or address of these elements, 27 are denoted by i , j , ϕk . For example, the ~~very~~ top element 28 has an index $i=0$ (0th column), $j=4$ (4th row), and ϕk represents the directivity of this individual element, either produced by an active element or element set alignment or by connecting a specific, k th member of an underlying stack of elements, having the appropriate orientation fixed, of which the figure shows only the top member. As another example element 29 has an index $i=1$ (-1st column), $j=1$ (1st row), and ϕk .

In FIG. 6B the directivity angle to the preferred direction 22 is ~~180° and~~ [180° and] the prior locations of the GW crests 61 are behind the GW crest 25. The distance between the lines (or planes comprising the GW wave crests) at elements in the GW direction 21 is 24. The elements 26 on the anticipated GW crest 25 of the GW 21 are connected to an information processing

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

device, that is interrogated (detection mode) or energized (generation mode). In FIG. 6C the future locations of the GW crests 60 is in front of the GW crest 25 and the directivity angle is ~~135E~~ [135°], in FIG. 6D it is ~~90E~~ [90°], in FIG. 6E it is ~~45E~~ [45°] and in FIG. 6F it is ~~0E~~ [0°].

In FIG. 7 is illustrated a spherical set of element sets or subsets or electrodes 31 comprising an element having directivity angles α_k and δ_k for a kth member of the element set or subset 32 distributed over a sphere 33.

A propulsion system utilizing a gravitational wave generator is shown in block diagram form in FIG. 8. As shown therein, the propulsion system provides a gravitational wave generator 67 disposed with [within] a vehicle housing 75. The generator includes a particle-beam source 69 [energizing elements] and nuclear-reaction chamber 72[, which includes the target-mass energizable elements. Such elements could involve high-energy, nuclear-particle collisions whose products are distributed asymmetrically in the direction of the particle-beam energizing element's motion (as discussed by Charles Seife (2001), Science, Volume 291, Number 5504, p. 573 and incorporated herein by reference). Alternatively, the energizable nuclear elements could be constrained to a preferred orientation yielding a preferred direction of the collision products and again, a nuclear jerk in a preferred direction. Such GW directivity is illustrated schematically in FIGS. 8A and 8B of the parent patent, U.S. 6,160,336]. The rearward moving gravitational waves 62 exit the rear of the vehicle propelling the vehicle in the desired direction of travel 74. The target-mass energizable elements in the nuclear-reaction chamber 72 build up, by constructive interference or reinforcement, the coherent GW 62 as exhibited in FIG. 4. The system of energizable elements comprising the target emulates a more extensive mass having a longer effective radius of gyration 10 exhibited in FIG. 1A and,

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

therefore, stronger GW and more momentum to cause the forward motion in the desired direction of travel 74. The
5 ~~forward-propelling~~ [A refractive medium can intercept the oppositely or forward-directed GW and those rays can be bent or refracted to the side in order to reduce the forward component of GW momentum and, thereby promote forward propulsion in the desired direction of travel. The forward-moving] portion of the
10 GW generated by the jerks associated with the energization of the elements comprising the target mass is not coherent. This GW portion is the result of the smaller actual radii of gyration of each individual energizable element. Thus weaker GW is generated and [as previously mentioned, can be bent to the side by a GW
15 refractive medium and] far less momentum is carried away to counter the propulsion in the desired forward direction of travel so that forward propulsion dominates.

The present invention relies upon the fact that the rapid movement or jerk or oscillation of a mass or collection of
20 submicroscopic particles such as nuclei will produce a quadrupole moment and generate useful high-frequency, for example, up to ~~TeraHertz (THz)~~ [QuadraHertz (Qhz) or higher frequency], GW. The device described herein accomplishes GW generation in several ways based upon the interaction of energizing and energizable
25 submicroscopic particles.

In a preferred embodiment a collection of target nuclei or target-beam particles are jerked or otherwise set in motion, for example, harmonic oscillatory motion, in concert, in response to the impact of a particle beam, which is a directed flow of
30 particles or waves that carries energy and information. The particle beam moves with the same speed as the local speed of the gravitational waves. According to [Ning Li and] Douglas Torr and ~~Ning Li~~ (1992), Physical Review B, Volume 64, Number 9, ~~p.5489~~ [p.5491], if the target is a superconductor, then the GW are
35 estimated to be two orders of magnitude slower than the speed of

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

GW in a vacuum or the speed of light. [Specifically, they state:
"It should be pointed out that since nothing is known of the
5 phase velocity of a gravitational wave ...propagating within a
superconductor, it is usually presumed to be equal to the
velocity of light. We argue that the interaction of the coupled
electromagnetic and gravitoelectromagnetic fields with the Cooper
pairs in superconductors will form a superconducting condensate
10 wave characterized by a phase velocity $v_{p\eta}$. Since ...the phase
velocity can be predicted for the first time as

$$v_{p\eta} = \dots 10^6 \text{ [m/s]} \quad (30)$$

which is two orders of magnitude smaller than the velocity of
light."]

15 The target will exhibit an absorption thickness, that is,
a length over which many of the impacting particles interact with
the target nuclei to produce a nuclear reaction whose collision
products move in a preferred direction resulting in a jerk or
oscillation.

20 The particle beam is composed of bunches of particles
generated in a cylindrical beam pipe, each bunch enters the
target material and interacts with a cylinder of target nuclei
or target beam particles, comprising the target mass, having a
length that is associated with the radius of gyration of the
25 emulated target mass. The results of the interaction, in
addition to the jerk or oscillation imparted to the target mass
by nuclear reaction or collision, include back-scattered
particles 5, secondary electrons 6, sputtered particles,
forward-scattered particles (channeling) and recoil atoms as well
30 as ion implantation.

The jerk-producing or oscillation-producing collisions
involve elastic (single Coulomb) and inelastic (bresstrahlung)
scattering impacts on nuclei and particles and sometimes result
in a nuclear reaction, the products of which move out in a
35 preferred direction based upon the alignment of the target 22.

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

The particle beam ~~bunches~~ [bunch's] front edge strikes the nuclei or particles in the cylindrical target-mass volume at a speed
5 equal to the local GW speed. As each nucleus or other particle-beam target is impacted and is jerked or otherwise set in motion by the reaction to a nuclear products emission or collision, it generates GW in the direction of or normal to the
10 ~~beam-s~~ [beam's] velocity and/or the alignment direction at the target nuclei and the GW grows in amplitude and emulates a large target mass having an effective radius of gyration larger than that of any single energizable element.

The GW can also be generated in the direction normal to a quadrupole (harmonic-oscillator) axis or in the direction of a
15 jerk, so that the particle-beam directed GW builds up or accumulates and generates a coherent GW as the beam particles progress through the target nuclei and thereby, emulates an extensive target mass. According to Douglas Torr and Ning Li (1993), Foundation of Physics Letters, Volume 6, Number 4, p.371
20 ~~A-[".]~~ . . . the lattice ions, . . . must execute coherent localized motion consistent with the phenomenon of superconductivity.@["] Thus, a preferred embodiment is to have the target nuclei constrained in a cylindrical superconductivity state. As the particle-beam bunch moves down the cylinder of
25 target nuclei, it strikes one target nuclei after another, creating a GW and adding to the forward-moving or radially-directed ~~GW-s~~ [GW's] amplitude as it progresses in step with the ~~bunch-s~~ [bunch's] particles in [the preferred] direction [in space of FIG. 1A] 22 thereby emulating an extensive target
30 mass. The particle-beam bunches are modulated by a particle-emission and/or chopper-control computer to impart information by modulating the generated GW. In addition, since the GW can be slowed by virtue of passing through a medium such as a superconductor ~~(Torr[(Li] and Li, [Torr] op.cit. 1991)~~
35 [1992]) and, therefore, refracted by it, as in a lens, the GW can

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

be focused and intensified. [The GW can also be generated in a direction normal to a dipole axis. According to Joseph Weber
5 (1964), Gravitation and Relativity, W. A. Benjamin Inc., New York, p. 91, a summation of charge times acceleration gives rise to dipole radiation, which also can be accomplished gravitationally in a superconductor according to Li and Torr, op. Cit. 1992, pp. 5489ff and Torr and Li, op. Cit. 1993, pp. 371ff.]

10 In another embodiment, electron transfer dynamics between incident particle-beam-gas molecule energizing elements, for example, nitric oxide, NO and a metal target surface composed of energizable elements such as Au (111) has been discussed by Yuhui Huang et al. (2000), Science, Volume 290, No. 5489, pp. 111-114.
15 The large-amplitude vibrational motion associated with the energizable target molecules in high vibrational states strongly modulates the energy driving force of the energizing electron-transfer reaction. In this regard, although not discussed in any connection with GW generation, according to
20 Huang, et al. (ibid, p. 113), "[...]...the multiquantum vibrational transfer occurs on the subpicosecond time scale.@["]

In order to accomplish experiments or communication with a GW generation or transmitter device, it is necessary to detect or receive GW. In this regard Application Serial No. 09/616,683,
25 filed July 14, 2000, [now U.S. Patent 6,417,597,] describes such a detection device in which the collector elements replace the energizable elements of the present invention. The GW receiver is oriented in a direction from which the GW is known to be generated. The GW can be focused on the detection device by
30 means of a refractive medium exhibiting a lense shape, as shown in FIG. 2, in order to amplify the GW intensity. Furthermore, since the GW frequency is also known, the collector elements of the GW receiver can be interrogated, that is, selectively connected by the control computer to an information-processing
35 device, in a sequence at the anticipated incoming GW frequency[,

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

that is, tuned]. Thus, as the incoming GW pass through the ensemble of the GW ~~receiver-s~~ [receiver's] collector elements, utilizing piezoelectric crystals, or capacitors, or strain gauges, or transducers, or parametric transducers, or nanomachines, etc., these elements are interrogated at the anticipated time of passage of the GW crest past them.

The uncertainty is in the determination of the GW phases. Within, for example, a subpicosecond time resolution, all of the possible GW phases (or times that the GW crest hits the leading rows of collector elements) are initially swept through by the control computer to establish the phase that correlates best with the maximum amplitude of the received GW signal, that is, tuned to the GW signal. After this initialization the GW phase is tracked by, say, a Kalman filtering technique described on pp. 384-392 of Robert M.L. Baker, Jr. (1967) *Astrodynamics, Applications and Advanced Topics*, Academic Press, New York. The small voltages and currents produced by some of the alternative collector elements can be measured, for example, by a superconducting quantum interference device (SQUID) using Josephson junctions (described in U.S. Patent 4,403,189) and/or by quantum non-demolition (QND) techniques utilized in optics but applied to the problem of reducing quantum-noise limitations for high-frequency GW. The QND technique was first suggested by Vladimir Braginsky of the Moscow State University and published by A.M. Smith (1978) in ~~ANoise~~ ["Noise] *Reduction in Optical Measurement Systems*, @["] IEE Proceedings, volume 125, Number 10, pp. 935-941. [Superconductors are also contemplated for use in connection with the collection elements as discussed in the previous application, Serial No. 09/616,683, filed July 14, 2000, so that the collection elements can be in a superconducting state.

Referring again to U.S. Patent 6,417,597] ~~Referring again to Application Serial No. 09/616,683, filed July 14, 2000, it~~

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

describes collector elements that can detect GW through the same
conductors as are attached to the energizable elements for GW
5 generation and are connected by an Individual Independently
Programmable Coil System (IIPCS), a device that acts as a
transceiver. The IIPCS is more fully described in U.S. Patent
6,610,336. Such a control computer can connect the collector
elements together and interrogate them in a pattern that will
10 effectively sense GW incoming from a specific direction and, in
like fashion, it can connect the energizer elements and energize
them in a pattern that will effectively direct the radially or
linearly propagating GW or steer them in a specific direction.
It is valuable, therefore, both to scan for GW from a given set
15 of directions, and to steer GW in a given set of directions, that
is, to provide for directivity in both reception and transmission
of GW. The control computer, acting in concert with the
information-processing device, establishes a communications link
between a GW receiver and a GW ~~transmitters~~ [transmitter] or,
20 alternatively, ~~between~~ [among] GW transceivers and establishes
point to multipoint communication.

The aforementioned directivity can be best illustrated by
FIG. 6. FIG. 6A exhibits a plan view of a typical section of an
array of elements or element sets or subsets, the elements with
25 indices $i, j, \phi k$. ϕk represents the directivity angle,
measured relative to some arbitrary fixed direction in space ϕ ,
of an individual element, either produced by active element
alignment (by being in an electromagnetic field, in a
superconducting state, spin polarized, etc.) or being an element
30 set or subset, or by connecting to a specific member of an
underlying stack of elements having the appropriate orientation
fixed, of which the figures shows only the top member. In this
latter case the i, j element stack may, for example, be 180
members high, each member offset from the next by one degree ($k=1$
35 to 180) in the three-dimensional ensemble of elements. The

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

central or control computer [or information processing] function is, therefore, a table look up of the indices that should be
 5 ~~None~~["on"] for a given directivity and also located on the crest of the specific GW of interest (incoming or outgoing). An ~~None~~["on"] element is one that is interrogated (for reception) or energized (for transmission).

In FIG. 6B the directivity angle to the preferred direction
 10 22 is ~~180E~~ [180°]. The elements on the anticipated GW crest 25 of interest of the GW 21 are communicated to collectors and interrogated (detection mode) or energized (generation mode). The prior locations of the GW crests 61 are behind the crest 25. In FIG. 6C the directivity angle is ~~135E~~ [135°], and the future
 15 locations of the crests 60 are in front of the crest 25. In FIG. 6D the directivity angle is ~~90E~~ [90°], in FIG. 6E it is ~~45E~~ [45°], and in FIG. 6F it is ~~0E~~ [0°]. A coordinate rotation will afford directivity in three dimensions. In this latter regard, the elements could be arrays of elements or element sets or
 20 subsets and those arrays could be spherically isotropic in their activity as either collectors or energizable elements. In one embodiment, the element sets or subsets consist of piezoelectric crystals in a spherical configuration or array. Thus, GW can be sensed or generated in any direction. In this case, the
 25 piezoelectric crystals would be spread out evenly over the surface of a sphere 33 exhibited in FIG. 7. In a preferred embodiment each element would consist of a spherical piezoelectric crystal 33 with electrodes 31 spread out evenly over its surface and interrogated or energized in opposite pairs
 30 to achieve directivity in detection or generation of GW.

FIG. 7 illustrates the sphere 33 and the elements 31 (collectors or energizable) comprising the element sets or subsets. A typical member of this element set or subset, 32, has its directivity angles α_k and δ_k for the kth member of the element
 35 sets or subsets defined by the notation ~~kk~~ $\{\phi_k, (\alpha_k, \delta_k)\}$. In one

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

embodiment, the elements are piezoelectric crystals. In a preferred embodiment the elements are electrodes 31 attached to the surface 33 of a single, spherical piezoelectric crystal. Thus the propagation of the GW can be steered as opposite pairs of the electrodes are energized and detected from specific directions as the opposite pairs of electrodes, acting as collectors, are interrogated. Collectively the myriad of such spherical piezoelectric crystals can generate or detect a coherent GW by energizing or interrogating them in an appropriate pattern or sequence as illustrated in FIGS. 6B, 6C, 6D, 6E, and 6F.

15 Numerical Example

The specific relationship for GW generation by energizing elements, such as particle-beam particles, colliding with energizable elements, such as aligned target nuclei, will be an outcome of the use of the present invention described herein. To better understand that relationship, it is helpful to refer to the standard quadrupole approximation, Eq. (110.16), p.355 of L.C. Landau and E.M. Lifshitz, The Classical Theory of Fields, Fourth Revised English Edition, Pergamon Press, 1975 or Eq. (1), p.463 of J.P. Ostriker, ~~(Astrophysical~~ ("Astrophysical Source of Gravitational Radiation in Sources of Gravitational Radiation, [" Edited by L.L. Smarr, Cambridge University Press, 1979) which gives the GW radiated power (watts) as

$$P = -dE/dt = - \cancel{(G/45c^5)} [(G/45c^5)K] (d^3D_{\alpha\beta}/dt^3)^2 \text{ [watts]} \quad (1)$$

where

30 E = energy [joules],

t = time [s],

G = 6.67423×10^{-11} [m³/kg-s²] (universal gravitational constant, not the Einstein tensor),

c = 3×10^8 [m/s] (the speed of light), and $D_{\alpha\beta}$ [kg-m²] is the quadrupole moment-of-inertia tensor of the mass of the target

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

particles, and the δ and β subscripts signify the tensor components and directions. [The quantity $(d^3D_{\alpha\beta}/dt^3)^2$ is the
5 kernel at the quadrupole approximation.]

Equation (1) can also be expressed as:

$$P = \cancel{6K} \cancel{I^3 \dot{I}} (d^3I/dt^3)^2 / 5 (c/2)^2 [K_{I^3 \dot{I}} (d^3I/dt^3)^2 / 5 c^2] \text{ [watts]} \quad (2)$$

where $I = \sum m r^2 [(\sum m) r^2]$ [kg-m²], the moment of inertia,

$\sum m [(\sum m)]$ = sum of the masses of the individual target nuclei
10 that are impacted by the particle beam, expel nuclear-reaction products, and caused to jerk or recoil in unison, [kg], (or, at least jerk or oscillate as the forward-moving GW front moves by),

r = the effective radius of gyrations of the ensemble of target nuclei that constitute the target mass [m], and $\cancel{K I^3 \dot{I}}$
15 [$K_{I^3 \dot{I}}$] = a dimensionless constant or function to be established by experiment.

The third derivative of the moment of inertia is

$$d^3I/dt^3 = \cancel{2 \sum m d^3r^2/dt^3} = \cancel{2 \sum r^2 m d^3r/dt^3} + \cancel{2 \sum r^2 m d^2r/dt^2} + \dots [(\sum m) d^3r^2/dt^3 = 2 r(\sum m) d^3r/dt^3 + \dots] \quad (3)$$

20 and d^3r/dt^3 is computed by noting that

$$\cancel{2 r \sum m d^2r/dt^2} = \cancel{n^2 r / n} [2r(\sum m) d^2r/dt^2 = n^2 r f_n; [N-m] \text{ (equation of motion)}] \quad (4)$$

where n is the number of beam particles, which interact with target nuclei to emit nuclear-reaction products, and $\cancel{f_n} [f_n]$ is the
25 nuclear reactive force on a given target nuclei caused by the release of nuclear-reaction products. The third derivative is approximated by

$$d^3I/dt^3 \approx \cancel{n^2 r^2 / n} / \Delta t [= n^2 r \Delta f_n / \Delta t] \quad (5)$$

in which $\Delta \cancel{f_n} [f_n]$ is the nearly instantaneous increase in the
30 force on the ensemble of nuclei caused by the release of nuclear-reaction products or the collision impulse over the brief time interval, Δt . The Δt is the nuclear-reaction time for a typical individual collision, taken here to be 10^{-12} [s]. We will also take, for convenience of calculation, the time between
35

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

emission of particle bunches also to be Δt . Thus the chopping frequency would be one THz.

5 As a bunch of beam particles strike the target nuclei material, the particles impact on the target nuclei, with, for example, 10% of them causing a nuclear reaction. In this regard, the characteristic length (or [emulated or effective] radius of gyration, r) of the target mass could be considered to be the
10 thickness of the target mass or the distance that the particle-beam bunch moves at local GW speed before the number of particles in a given bunch is reduced by half or by some other measure of the effective radius of gyration of the target mass as the ensemble of energized particles comprising the target mass
15 move in concert at local GW speed and emulate a cohesive target mass. The target nuclei are held in place by intermolecular forces that propagate at the local sound speed, that is, during the Δt interval while the beam particles interact with the target nuclei and create aligned nuclear-reaction products, the
20 particles move at a distance $v\Delta t$, where v is the particle speed that is made equal to the local GW speed, V_{GW} , but the nuclei move more slowly and influence one another at sound speed. Thus, alternative characteristic lengths could be either $v\Delta t$ or the distance local sound travels in Δt or the length of the
25 target-mass cylinder, or the absorption thickness, etc.. For the numerical example we will choose $r = 1$ [cm] = 0.01 [m] and the beam itself to have a cross-sectional area of one square centimeter. Thus for the numerical example the target mass is a cube one centimeter on a side and the generated GW rings from
30 harmonic oscillation that move out in a plate or slab one centimeter thick.

With $K_{I3dot} = \pm$ [32], as in the case of the GW radiated by the centrifugal-force jerk of a spinning rod, from Eq.(1), p.90 of Joseph Weber (1964), ~~AGravitational~~["Gravitational] Waves @in

35

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

Gravitation and Relativity, ["] Chapter 5, W.A. Benjamin, Inc., New York and introducing Eq.(5), Eq.(2) becomes

5
$$P = 1.76 \times 10^{-52} (n \Delta \frac{f_n}{\Delta t})^2 [f_n / \Delta t]^{21} [\text{watts}]. \quad (6)$$

The number of particles in a typical bunch is estimated to be approximately that of the Stanford Linear Collider (SLC) or 4×10^{10} particles. It is estimated that 10% of the particles impact target nuclei and result in nuclear reaction (that is, a 10% harvest), so $n = 4 \times 10^{10}$. Inserting these numbers into Eq.(6) we have

10
$$P = 1.764 \times 10^{-52} \frac{(4 \times 10^{10} \times 2 \times 0.01 \Delta f_n / \Delta t)^2 [(4 \times 10^{10} \times 2 \times 0.01 \Delta f_n / \Delta t)^{21}]}{[f_n / \Delta t]^{21}} [\text{watts}] \quad (7)$$

and, subject to further verification as to the mass defect and impulsive nuclear force, that is verification of the magnitude of the jerk, we take $\Delta f_n = 1 \times 10^{-6}$ [N] and $\Delta t = 10^{-12}$ [s] resulting in

15
$$P = 1.13 \times 10^{-22} [\text{watts}].$$

The reference area is either the rim of a disk one centimeter thick and one centimeter in diameter or 3.14×10^{-4} [m²] for a GW flux of 3.6×10^{-19} [watts/m²] for a harmonic oscillation [of the target elements] or one square centimeter for a linear jerk leading to a GW flux of 1.13×10^{-18} [of the target elements (there is a factor of 0.5 since the GW is bifurcated -- half moving in the direction of the jerk and half in the opposition direction). The former leads to a forward component of GW flux of 5.65×10^{-131} [watts/m²]. A lens system composed of a media in which the GW is slowed (such as a superconducting media) could concentrate or focus the GW from, say, a one square centimeter, to ~~10 micrometers~~ ²¹ [10 micrometers²¹] for an increase in GW flux of 10^6 to ~~1.13 x 10⁻¹²~~ ¹³¹ [5.65×10^{-131}] [watts/m²]. Note that in the refraction medium the GW wavelength is significantly smaller than 10 micrometers²¹ at THz frequencies, so that GW diffraction, if present, is not very significant. All of the foregoing quadrupole equations are approximations to P. Due to

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

the slowness of the GW, [about] one hundredth of light speed, the GW wavelength in the superconducting target is about

5 $\lambda_{GW} 0.01c\Delta t = 3 \times 10^6 \times 10^{-12} = 3 \times 10^{-6} [m]$, but still larger than the radius of the target nuclei, beam particles, or nuclear-reaction products, ~~or r , so $\lambda_{GW} \gg r$ and also~~ [so λ_{GW} is much greater than the radius of the target particles and also,] due to the slow propagation speed, all speeds \ll [are much less than] c . Thus the

10 quadrupole approximation is good, but still K_{I3dot} will be further refined as will the harvest and other details of the energizing and jerk-producing or harmonic-oscillation-producing mechanism of the invention such as Af_n and Δt . ~~In fact, as noted by C. W. Misner, K. S. Thorne, and J. A. Wheeler in Gravitation (1973),~~

15 ~~W. H. Freeman and Company, New York, p. 989, Eq. (1) is "...perhaps approximately (valid) for fast-moving or strong field sources."~~ [The GW produced also is "...itself the source of some additional gravitational field" as noted by Landau and Lifshitz (op cit, 1979, p. 349) and discussed in the Propulsion section

20 of U.S. Patent 6,417,597. Thus attendant to the GW is a change in gravity that can be effectively utilized for the movement of mass and, hence, as a propulsion means.]

Analysis of Binary Pulsar PSR 1913+16

25 As discussed in the Prior Application Serial No. 09/616,683, [now U.S. Patent 6,417,597,] since binary pulsar PSR 1913+16 represents the only experimental confirmation of GW, the features and advantages of the present invention will be better understood by a further analysis of this double-star system.

30 According to Robert M.L. Baker, Jr., p. 3 of ~~APreliminary~~ ["Preliminary] Tests of Fundamental Concepts Associated with Gravitational-wave Spacecraft Propulsion, @["] Paper No. 2000-5250 in the CD-ROM proceedings of the American Institute of Aeronautics and Astronautics Space 2000 Conference

35 and Exposition, AIAA Dispatch: dispatch@lhl.lib.mo.us, or

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

www.aiaa.org/publications, September 19-21, 2000, the double star
exhibits a mass of $m = 2.05 \times 10^{30}$ [kg], a semi-major axis, a , of
5 2.05×10^9 [m], and a mean motion, n (or ω) of 2.25×10^{-4}
[radians/s]. The average centrifugal force component or
force-vector component subject to change during the star-pair-s
[pair's] orbit, $\Delta f_{cfx,y}$, is

10
$$m a n^2 = (5.56 \times 10^{30}) (2.05 \times 10^9) (2.25 \times 10^{-4})^2 = 5.77 \times 10^{32} \text{ [N]}. \quad (8)$$

From Eq. (1), p. 90 of Joseph Weber, (op cit, 1964) and from
Eq. (2) herein[,] one has for ~~Einstein-s~~ [Einstein's]
formulation (1918, Sitzungsberichte, Preussische Akademi der
15 Wisserschaften, p. 154) of the gravitational-wave (GW) radiated
power of a rod spinning about an axis through its midpoint,
having a ~~time-constant~~ moment of inertia, I [kg-m²], and an
angular rate, ω [radians/s]:

20

25

30

35

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

$$P = -32GI^2\omega^6/5c^5 = -G(I\omega^3)^2/5(c/2)^5 \text{ [watts]} \quad (9)$$

5 or

$$P = -1.76 \times 10^{-52} (I\omega^3)^2 = -1.76 \times 10^{-52} (r[rm\omega^2]\omega)^2 \quad (10)$$

where [using classical (not relativistic) mechanics,] $[rm\omega^2]^2$ can be associated with the square of the magnitude of the ~~rod's~~ [rod's] centrifugal-force vector, f_{cf} , for a rod of mass, m , and radius of gyration, r . This vector reverses every half period at twice the angular rate of the rod (and a ~~component's~~ [component's] magnitude squared completes one complete period in half the ~~rod's~~ [rod's] period). Thus the GW frequency is 2ω and
 15 the time-rate-of-change of the magnitude of, say, the x-component of the centrifugal force, f_{cfx} is

$$\Delta f_{cfx}/\Delta t = [\Delta f_{cfx}/\Delta t] 2f_{cfx}\omega. \quad (11)$$

(Note that frequency, $\nu = \omega/2\pi$.) The change in the centrifugal-force vector itself (called a ~~Ajerke~~ ["jerk"] when divided by a time interval) is a differential vector at right angles to f_{cf} and directed tangentially along the arc that the dumbbell or rod moves through. As previously mentioned, Equation
 25 (9) is an approximation and only holds accurately for $r \ll \lambda_{GW}$ (wave length of the GW) and for speeds of the GW generator far less than c (the speed of light).

Equation (9) is the same equation as that given for two
 30 bodies on a circular orbit ~~(also exhibiting a time constant moment of inertia)~~ on p. 356 of Landau and Lifshitz, op[.] cit[.], 1975, ($I = \mu r^2$ in their notation) where $\omega = n$, the orbital mean motion.

35

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

As a validation of the use of a jerk to estimate gravitational-wave power, let us utilize the jerk approach for computing the gravitational-radiation power of PSR1913+16 [PSR 1913+16]. We computed in Equation (8) that each of the components of force change, $\Delta f_{cfx,y} = 5.77 \times 10^{32}$ [N] (multiplied by two since the centrifugal force reverses its direction each half period) and $\Delta t =$

10 ~~(2)(7.75hrx60minx60sec)~~ $[(1/2)(7.75hrx60minx60sec)] = 1.395 \times 10^4$ [s].

Thus using the jerk approach:

$$P = -1.76 \times 10^{-52} \{ (2r\Delta f_{cfx}/\Delta t)^2 + (2r\Delta f_{cfy}/\Delta t)^2 \} =$$

$$-1.76 \times 10^{-52} (2 \times 2.05 \times 10^9 \times 5.77 \times 10^{32} / 1.395 \times 10^4)^2 \times 2 = -10.1 \times 10^{24} [\text{watts}] \quad (12)$$

15

versus ~~-9.78x10²⁴~~ $[9.296 \times 10^{24}]$ [watts] using Landau and Lifshitz's [Lifshitz's] (op[.] cit[.], 1975, p. 356) more exact formulation given by the analyses of Baker (op[.] cit[.], 2000, p. 4) integrating using ~~(more correctly)~~ the mean anomaly, ~~not the true anomaly~~. The [stunning] closeness of the agreement is, of course, fortuitous since due to orbital eccentricity there is no symmetry among the $\Delta f_{cfx,y}$ components around the orbit. Nevertheless, the value of the jerk approach is well demonstrated!

25

APPLICATION OF THE INVENTION TO COSMOLOGY

Since the present invention produces waves or ripples in the conjectured spacetimeuniverse (STU) continuum or fabric (see U.S. Patent 6,160,336), it can be used to explore cosmological conjectures and theories. According to a thumbnail sketch of Einstein's theory of general relativity, time and space disappear with material things. That is, matter (stars to atomic nuclei) are inseparably connected to time and space and vice versa. "Things" are all but hills, valleys, and holes in the fabric of

35 Einstein's spacetime.

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

It is conjectured that the equivalence of inertial and attractive mass and the unification of all forces, gravitational, centrifugal, electromagnetic, nuclear, etc. is that they are all simply undulations in the multidimensional STU fabric. We may consider a centrifugal force field to be a gravitational force field and elastic, thrust, drag, etc., force fields to be electromagnetic in origin. Thus force is a property of STU and vice versa. Such a concept is similar to that expressed by Schrödinger in 1946 (reported in Denis Brian's Einstein a life, 1996, John Wiley & Sons, p. 351) in his theory that "...purely wave theory, in which the structure of space-time would yield gravitation, electromagnetism, and even a classical analog of strong nuclear (forces)". In fact, the term "gravitational waves" could be replaced by the term "force waves" or ~~inertia~~["inertia] waves@["] since it is the change in force, any force or attraction, or jerk of an inertial mass that results in the waves or ripples in the STU fabric.

Gravitational waves are related directly to an inertial mass in motion (caused by either a change in attraction or force --a jerk or harmonic oscillation) and not directly related to a gravitational field. In this regard, the wave/particles for such a force wave are proposed to be defined as ~~@forceons@ or @massons@~~["gravitational instantons" or "instantons"]. Such wave/particles would be analogous to photons associated with electromagnetic waves, gravitons associated with gravitational attraction, and gluons associated with strong nuclear forces. For historical reasons the term gravitational waves should be retained, whereas to avoid confusion with gravitons and the erroneous association of GW exclusively with gravitational attraction the term ~~forceons or massons should be coined. (A less attractive term, Ajerkons" should be avoided even though it is a jerk that creates the GW.)~~["gravitational instantons" or "instantons" is used.]

1 40702/RJW/B596

SUBSTITUTE SPECIFICATION

There is a fundamental difference between photons, gravitons, gluons, etc., and ~~forceons or massons~~ [instantons].

5 The former are manifested by the curvature of the multidimensional STU fabric created by the attractions or forces associated with charge, mass, nuclear particles, etc. (all conjectured to be similar to gravity, that is, not really "forces", but motion along convergent or divergent geodesics in

10 the multidimensional STU), whereas the latter is manifested by the rapid changes in the forces or jerk [or oscillation] associated with the former - like ["cracking a whip" or "striking a drum head"] of STU [fabric] to produce ripples in the STU fabric [as Landau and Lifshitz (op cit, p. 355) suggest, such

15 STU fabric distortions caused by high-frequency gravitational waves (expressed as instantons) change gravity (expressed as gravitons) itself]. Thus all the properties of wave/particles, like diffraction [and dispursion], may not be present in the ~~forceons or massons~~ [instantons].

20 Continuing with the thumb-nail-sketch conjectures of the STU continuum at the most elementary level, ~~the equivalence of the inability to define position and velocity simultaneously~~ and the inherent uncertainty in position and velocity [(as opposed to the practical, experimental inability to exactly define position and

25 velocity simultaneously)] is simply a reflection of the fact that you can't "see" the entire STU panorama from any one single vantage point. Thus there can be complete determinism, cause and effect can prevail, and "God does not have to play dice", because everything is in the STU fabric, for example, in different

30 universes at different times everything cannot be "seen". A "line" cannot connect ~~Apoints~~ ["points"] in the STU fabric, but the ~~Apoints~~ ["points"] are still there and their "motion" on the fabric is predictable; but, unfortunately, they can't be ~~Aseen~~ ["seen"] or predicted simultaneously. The more conventional

35

1 40702/RJW/B596


SUBSTITUTE SPECIFICATION

spacetime continuum is embedded in the multidimensional STU, which is a multidimensional manifold.

5 As far as quantum mechanics is concerned, the detailed surface of the STU fabric can be thought of as ribbed or like steps - essentially quantum steps. According to this conjecture the intractable frontier between ~~A~~["]... a smooth spacial geometry..." and "...the violent fluctuations of the quantum
10 world on short distances...the roiling frenzy of quantum foam." (Brian Greene, 1999, the elegant universe, Norton, New York, p. 129) is nothing more or less than the interface between osculating universes on small scales in which entities shift back and forth at will -- actually smooth transitions with mass/energy
15 and momentum conserved and entropy constant. Thus the measurement of the fundamental constants in a given universe are subject to a very small variation depending upon ~~Awhere~~["where"] (or ~~Awhen~~["when"]) they are measured.

In this regard, ~~Awhere~~["where"] has a more global meaning.
20 In the STU ~~Awhere~~["where"] is similar to position in conventional space (but a continuum of dimensions). On the other hand ~~Awhere~~["where"] and ~~what~~[""] are time-like universe dimensions. In ~~Aour~~["our"] universe its simply ~~Atime~~["time-]when.@[""] These extremely simplified general
25 cosmological conjectures would require very complicated mathematics in order to obtain quantitative results and make them more than just superficial fantasies. Thus the present invention would be useful in obtaining experimental insights concerning the foregoing conjectures and confirmation of quantitative
30 cosmological theories and predictions. Also the receiver aspect of the invention, as it relates to the detection of high-frequency GW, would be useful in studying the ~~A~~Big["Big"] Bange[""] information imprinted on GW background between [about] 10^{-25} and 10^{-12} [s] after its start.

35



INVESTMENT OPINION REPORT

RESEARCH AND KNOWLEDGE BEFORE INVESTING

-- Special Situation & Alert --

NAME:	Eternal Technologies Group	Outlook:	STRONG GROWTH
TICKER:	(OTCBB: ETLT)	Sh. Outstanding:	25.5 million
INDUSTRY:	Biotech/ Pharmaceuticals		

-- Animal genomics and biopharmaceutical R&D for the Chinese market--

TRADING STATISTICS

Recent Price:	\$0.90	12 Month Trading Range:	\$0.42 - \$1.70
Avg. Volume:	11,988 shares	Market Capitalization:	\$22.9 million

ETLT- A Profitable Player in the \$340 Billion Animal Genetics Research Industry

Over 10,000 years ago in the lower Yangtze River valley in China, mankind first bred domestic animals to ensure a steady and viable food supply as the fundamental building block of a stable economy. Today, with a population of over 1.3 billion, the demand for new and more productive methods of animal husbandry in China is just as important a component of economic development, and the region has emerged as a focal point of animal genetic research. Eternal Technologies Group has emerged to meet this demand, and is one of the leading animal genetics and biopharmaceutical R&D firms in China with strong ties to the government and diversified operations in animal genomics and breeding, dairy and meat production, and biopharmaceutical research.

The Company has already demonstrated profitability, a rarity in a biotechnology industry where hundreds of millions of dollars are often spent before revenues are ever recorded, with FY 2002 earnings of \$0.26 per share and gross margins of 78% on revenues of \$12.6 million. Unlike most companies in the biotech industry, Eternal Technologies has developed a solid and recurring source of revenues with its operations in animal breeding and meat production which provide it with a solid footing to pursue additional opportunities in an animal genetics research and biopharmaceutical drug production. ETLT is working to develop a drug to treat thrombosis, Thrombreaker, and is bringing anti-cancer drugs into the pipeline.

With its position at the forefront of an explosive growth animal genetics research industry estimated at \$340 billion worldwide by the US Department of Agriculture, ETLT is capitalizing on the "potentially huge opportunity for biotech firms engaged in animal genetics research" (Red Herring, May 2002). The biotechnology industry is one of the hottest performers in the market today with the NASDAQ Biotech Index up over 35% since January. With biotech firms trading at an average TTM P/E of 30x, Eternal's trading levels at roughly 4x earnings make it a tremendous growth opportunity. With new drug developments in the pipeline, established and growing revenues, and a strong position in the developing Chinese market, we would like to present you with ETLT as a compelling investment that you cannot afford to overlook.

This Investment Opinion Report provides information on selected companies that IOR believes have investment potential. IOR is not a registered advisor or broker-dealer. This report is provided as an information service only, and the statements and opinions in this report should not be construed as an offer or solicitation to buy or sell any security. IOR accepts no liability for any loss arising from an investor's reliance on or use of this report. An investment in ETLT considered to be highly speculative and should not be considered unless a person can afford a complete loss of investment. IOR has been retained to distribute this report on ETLT and has been paid one hundred thousand shares. IOR and its officers and directors may from time to time buy or sell ETLT common shares in the open market without notice. This report contains forward-looking statements, which involve risks and uncertainties that may cause actual results to differ materially from those set forth in the forward-looking statements. For further details concerning these risks and uncertainties, see the SEC filings of ETLT including the company's most recent annual and quarterly reports.

IF YOU RECEIVED THIS FAX IN ERROR AND WOULD LIKE TO HAVE YOUR NUMBER REMOVED FROM OUR DATABASE, CALL TOLL-FREE AT 866-807-4238.

INVESTMENT HIGHLIGHTS:

Eternal Technologies Group (OTC BB: ETLT) is a diversified animal genetics and biopharmaceutical R&D firm focusing on the Chinese market. The Company has operations in animal breeding and embryo development; meat and dairy production; and biopharmaceutical research. With animal genetics research emerging as the new frontier in biotechnology, estimated at \$340 billion worldwide by the USDA, ETLT stands at the forefront of a huge and underserved market opportunity.

-Diversified operations afford near term profitability and revenue growth from animal breeding, embryo transfer, and dairy and meat production while long term biopharmaceutical opportunities are explored.

-With the largest hereditary gene pool of purebred sheep in China, and with 80% of the country's sheep embryo imports, ETLT is the dominant national player in animal genetics research.

-According to GENBANK, ETLT has been the first company to separate the gene for adder antithrombin, the most effective treatment for thrombosis, and has used its knowledge to develop its drug Thrombreaker.

-Solid sales forecasts with FY '02 revenues of \$12.6 million expected to reach \$29 million by FY '04. Efficient operations afford gross margin of 78%.

-Significant asset base with over \$7 million in cash and receivables and book value of \$0.96 per share.

-Trading at only 3-4x FY 2002 EPS of \$0.26, ETLT is significantly undervalued relative to the biotech industry which trades at an average P/E of 30x.

As it begins to develop and rollout new biopharmaceutical products from animal genetics research while continuing to grow its core revenues from animal breeding and meat production, we believe that Eternal Technologies Group will become one of the hottest players in the \$340 billion animal genetics research industry.

Additional information resources:

www.EternalPRC.com